


PV LAMINATE STRIPS

FLEX SERIES 03-N

2585mm




PV LAMINATE FLEX SERIES 03N

Flexible PV Laminate strips are a innovative Solar solution unique to Metalcraft Solar. The FLEX PV modules adhere directly to the pan of 'espan470' roof profile; once installed they present the significant aesthetic advantages of an integrated PV solution, with high efficiency output properties.

Key features

- Record efficiency levels in a CIGS flexible form factor
- Low installed weight at less than 2.2 kg/m² (<0.5 lb/ft²)
- No penetrations, ballast or racking required
- Applicable for high wind load and high seismic hazard areas
- Bypass diodes reduce PV system shading losses
- Directly bonds to many approved surfaces



Reliability and safety

IEC 61646, IEC 61730, IEC 62716, Australia CEC, IEC 61701 (Salt Spray) UL 1703, cUL 1703

Warranty

5 year workmanship
10/25 year warranty against power loss

Electrical performance at stc¹

			FLEX-03 110N	FLEX-03 115N	FLEX-03 120N	FLEX-03 125N	FLEX-03 130N
Nominal Power	P _{MPP}	[W]	110	115	120	125	130
Aperture Efficiency	η	[%]	14.4%	15.0%	15.7%	16.4%	17.0%
Power Output Tolerance		[W]	+5/-0	+5/-0	+5/-0	+5/-0	+5/-0
Maximum Power Voltage	V _{MPP}	[V]	28.5	29.0	29.5	30.0	30.5
Maximum Power Current	I _{MPP}	[A]	3.87	3.97	4.07	4.16	4.26
Open Circuit Voltage	V _{OC}	[V]	36.5	36.8	37.1	37.4	37.7
Short Circuit Current	I _{SC}	[A]	4.70	4.70	4.70	4.70	4.70
Maximum Series Fuse Rating		[A]	10				
Maximum System Voltage	(IEC/UL)	[V]	1000/1000				

¹Standard Test Conditions (STC): 1000 W/m², 25°C cell temperature, AM 1.5 spectrum

Thermal characteristics

NOCT	[°C]	48
Temperature Coefficient of P _{MPP}	[%/°C]	-0.38
Temperature Coefficient of V _{OC}	[%/°C]	-0.28
Temperature Coefficient of I _{SC}	[%/°C]	0.008

Physical and mechanical specifications

Length	2585 mm (101.8 in)
Width	348 mm (13.7 in)
Thickness, Maximum at J-Box*, Module	17 mm (0.7 in), 2.5 mm (0.1 in)
Weight (Module without adhesive)	1.6 kg (3.6 lb)
Weight (Module with adhesive)	1.9 kg (4.3 lb)
Weight/Area (Module without adhesive)	1.8 kg/m ² (0.4 lb/ft ²)
Weight/Area (Module with adhesive)	2.2 kg/m ² (0.5 lb/ft ²)
Junction Box Type	IP68
Cable Connections	Amphenol Technology Shenzhen (E346053)
Cell Type	Copper Indium Gallium Diselenide (CIGS)
Warranty**	5 year workmanship; 10/25 year power output
Certifications	UL 1703, IEC 61646, IEC 61730, cUL 1703, IEC 62716, Australia CEC, IEC 61701 (Salt Spray)
Packaging Info	15 modules per crate, 150 modules per pallet, 600 modules per 20' ISO container, 2400 modules per 40' ISO container

.5 mm (0.1 in) for the rest of the module with adhesive
.6 mm (0.06 in) for the rest of module without adhesive
*Please see full warranty for details

