

# METDEK 855

## METDEK 855 EXPLAINED

The Metdek 855 Roofing and External Wall Cladding system comprises:

- › A long run steel sheet with a 60mm deep trough profile
- › Associated design and installation information

Metalcraft fabricates the Metdek 855 sheets from steel manufactured by New Zealand Steel. This steel is supplied with different protective coatings which are designed to withstand conditions in specific New Zealand Corrosion Zones. Refer to NZ Steel's Environmental Categories Brochure at [www.nzsteel.co.nz/technical-resources](http://www.nzsteel.co.nz/technical-resources) for details.

Metdek 855 is available in the following NZ Steel branded products:

- › Colorsteel® Endura®
- › Galvsteel®
- › Colorsteel® Maxx®
- › Zinalume®

In the following sizes:

- › Thicknesses: 0.4mm, 0.48 and 0.55mm
- › Width: Cover = 855mm Sheet = 925mm

And with the following profile dimensions:



## PURPOSE

Metalcraft Roofing supply the Metdek 855 system as an external vertical wall cladding and on roofs with a minimum pitch of 3 degrees.

## SCOPE OF USE

Metalcraft Roofing supply the Metdek 855 Roofing and External Vertical Wall Cladding system for use on residential and commercial buildings (most suited to large commercial buildings) within the following scope:

### LOCATION:

- › In wind zones:
  - › Up to and including Extra High as defined by NZS-3604:2011.
  - › Subject to specific engineering, if the engineer has satisfied themselves that the product, pitch and fixings will meet the conditions.
- › In all climate zones as defined by NZS-3604:2011, subject to the limitations set out below (see limitations overleaf).
- › On buildings located within 1m of the relevant boundary, in respect of fire spread only.

### BUILDING:

- › On new buildings that have been designed and constructed to comply with the NZ Building Code (NZBC) using timber or steel framing.
- › On existing buildings using timber and steel framing where the designer and installer have satisfied themselves that the building is suitable for the intended building work.
- › In conjunction with a vapour permeable building wrap that has a permeability of 36g/m<sup>2</sup>/day of a vapour resistance of no more than 500MNs/g.
- › In conjunction with a potable water collection system.



## VERSION:

*NOTE: Uncontrolled in printed format.*

## DATE:

**Name:** Frances Charles  
**Position:** National Sales & Marketing Mgr

Signed on behalf of: Metalcraft Roofing.

By signing this pass™ the signatory confirms that, in respect of the subject of this pass™, the company has met their s14G obligations under the Building Act 2004.

## FURTHER INFORMATION

For further product assistance please contact:  
[www.metalcraftgroup.co.nz](http://www.metalcraftgroup.co.nz)

To find your nearest Metalcraft Roofing branch visit [www.metalcraftgroup.co.nz](http://www.metalcraftgroup.co.nz)

## LIMITATIONS OF USE

### LOCATION:

- Metdek 855 may be used as a roof cladding system in exposure zones B, C & D. For use in "Microclimatic considerations," (as defined in Sec 4.2.4) refer to Metalcraft Roofing.
- Metdek 855 may be used as a wall cladding system in exposure zones B & C. Where Metdek 855 is to be used as a wall cladding in exposure Zone D, then only Colorsteel® Endura® or Colorsteel® Maxx® may be used.

### BUILDING:

- Where Metdek 855 is used in an insulated building in conjunction with steel framing, a thermal break is required.
- Contact with other materials must be in accordance with Table 21 (E2/AS1), or compatible with the The New Zealand Metal Roofing Manufacturers Association Inc (NZMRM) Code Of Practice.
- Building height and design wind speed is limited by the Metdek 855 design load span tables (refer to: [www.metalcraftgroup.co.nz](http://www.metalcraftgroup.co.nz)).
- Where it is used as a roof cladding system, Metdek 855 sheet lengths of ≤ 40m must be installed on a roof with a minimum pitch of 3°. Metdek 855 sheet lengths of > 40m but less than ≤ 60m must be installed on a roof with a minimum pitch of 4°.
- Metdek 855 can be used in conjunction with a potable water collection system.
- When used as a wall cladding, Metdek 855 must be installed in conjunction with a drained cavity.

## PERFORMANCE CLAIMS

If designed, installed and maintained in accordance with all Metalcraft Roofing requirements, the Metdek 855 Roofing and External Cladding system will comply with or contribute to compliance with the following provisions of the New Zealand Building Code:

Basis of compliance		
NZBC Clause	Means of compliance	Relevance
<b>B1 Structure</b> B1.3.1, B1.3.2, B1.3.3 (a, b, c, d, g, i)	<b>ACCEPTABLE SOLUTION</b> <b>B1/AS1</b>	<ul style="list-style-type: none"> <li>AS/NZS 1397:2011</li> <li>AS/NZS 1170:2002 (span tables)</li> </ul>
<b>B2 Durability</b> B2.3.1 (b)	<b>ACCEPTABLE SOLUTION</b> <b>B2/AS1</b>	<ul style="list-style-type: none"> <li>Coated in accordance with AS/NZS 2728:2013. (NZ Steel claim) cited in E2/AS1</li> </ul>
<b>C3 Fire Affecting Areas Beyond the Fire Source</b> C3.4(a), C3.5, C3.7 (a)	<b>ACCEPTABLE SOLUTION</b> <b>C/AS2-C/AS7</b> <ul style="list-style-type: none"> <li>Metals are non-combustible</li> </ul>	<ul style="list-style-type: none"> <li>ISO5660 BRANZ (FH 6102-TT, dated 3/1/2017) (Material Group 1-S)</li> <li>Steel non-combustible (refer para 5.8 C/AS2-C/AS7)</li> </ul>
<b>E2 External Moisture</b> E2.3.1, E2.3.2, E2.3.7 (a-c)	<b>ACCEPTABLE SOLUTION</b> <b>E2/AS1</b>	<ul style="list-style-type: none"> <li>NZMRM Code of Practice (v2.2)</li> </ul>
<b>F2 Hazardous Building Materials</b> F2.3.1	<b>ALTERNATIVE SOLUTION</b> <ul style="list-style-type: none"> <li>ColorCote safety data sheet</li> </ul>	<ul style="list-style-type: none"> <li>Coating system is inert once dry</li> </ul>

Basis of compliance		
Other performance claims	Means of compliance	Relevance
Metdek 855 Roofing and External Cladding system will not contaminate potable water	<ul style="list-style-type: none"> <li>AS/NZS 4020:2005</li> </ul>	<ul style="list-style-type: none"> <li>Claimed by manufacturer: NZ Steel</li> <li>BRANZ statement that metal roof suitable refer: <a href="http://www.level.org.nz/water/watersupply/mains-or-rainwater/harvesting-rainwater/">http://www.level.org.nz/water/watersupply/mains-or-rainwater/harvesting-rainwater/</a></li> </ul>

## USEFUL INFORMATION

Refer to [www.metalcraftgroup.co.nz](http://www.metalcraftgroup.co.nz) for information relating to:

- Technical information, drawings and specification.
- Specification of the correct fasteners.
- Care and maintenance.
- The Metalcraft Roofing warranty.

## NZ STEEL ASSURANCE

As the manufacturer of the steel from which Metdek 855 is fabricated, NZ Steel provides assurance that the steel:

- Has been manufactured in accordance with AS 1397-2001.
- Is coated in accordance with AS/NZS 2728:2013, or galvanized in accordance with AS/NZS 2312.2:2014.

## SOURCES OF INFORMATION:

- MBIE Acceptable Solutions
- AS/NZS-1397:2001 "Steel sheet and strip—Hot-dip zinc-coated or aluminium/zinc-coated"
- NZ Metal Roof and Wall Cladding Code of Practice (NZMRM) (V2.2)
- AS/NZS-1170:2004 "Structural design actions"
- AS/ NZS-2728:2013 "Prefinished/pre-painted sheet metal products for interior and exterior building applications"

## CONTACT INFORMATION

To find your nearest Metalcraft Roofing branch visit [www.metalcraftgroup.co.nz](http://www.metalcraftgroup.co.nz)

To find your nearest Metalcraft Roofing branch visit [www.metalcraftgroup.co.nz](http://www.metalcraftgroup.co.nz)